



Stainless Steel Ball Valve

3 Piece 4 Bolt, Swing Out Body, Full Port, Threaded x Square Flange Connection, Side Tap, Port Tap, Stainless Steel Trim, 1000 WOG

T-SS-1000N-4B NPT X SQUARE FLANGE W/SIDE TAP & PORT TAP



FEATURES

Type B Flange Face
Latch Lock may be Locked in Open or Closed Positions
29 in-Hg Vacuum Rating
100% Leak Tested
Wetted Surfaces Contain Less Than .25% Lead Content
Mating Flanges Available
Repair Kits Available

CERTIFICATIONS/APPROVALS

UL Listed

- MHKZ Manual valves
- YQNZ Compressed gas shut-off valves
- YRBX Flammable liquid shut-off valves
- YRPV Gas shut-off valves
- YSDT LP gas shut-off valves
- YQAR Anhydrous ammonia shut-off valves

MSS SP-110

NACE Certified


ANSI B16.11


ANSI B1.20.1

Conforms to API 598

Buy American Act Compliant

VALVE SEAT RATING 1000 WOG - 150 WSP





MATERIALS

No.	Part	Material
1	Body	CF8M Stainless Steel
2	End Cap (2)	CF8M Stainless Steel
3	Ball	CF8M Stainless Steel
4	Seat (2)*	Hostaflon® TFM 1600
5	Stem	316 Stainless Steel
6	Packing (2)*	RPTFE
7	Stem Seal*	Hostaflon® TFM 1600
8	Packing Gland	316 Stainless Steel
9	Body Seal (2)*	Hostaflon® TFM 1600
10	Handle	304 Stainless Steel
11	Handle Nut	304 Stainless Steel
12	Lock Washer	304 Stainless Steel
13	Body Bolt (4)	304 Stainless Steel
14	Body Lock Washer (4)	304 Stainless Steel
15	Body Nut (4)	304 Stainless Steel
16	Body Bolt (4)	304 Stainless Steel

^{*}Included in repair kit

DIMENSIONS

Part No	Size	Α	В	С	D	Torque
501-358	2"	5.43	4.25	7.81	1.97	480